

SHENZHEN INTERSKY CO., LTD win-win Cooperation

ROOM 228A,2ND FLOOR WEST, SCIENCE AND TECHNOLOGY INDUSTRIAL BUILDING, #6 KEYUAN ROAD,HI-TECH PARK, YUEHAI NANSHAN, SHENZHEN, CHINA.

SALES@SZINTERSKY.COM → 86 186 7552 1565

WWW.SZINTERSKY.COM

Ready Board

TY-RB32 Small Power Distribution Unit(SPDU)

0

-

Brief Introduction


TY-RB32 is a portable, safe, economic and easy to use prewired low voltage ready board with 3(Three) sockets 1(One) lighting lamp and protection area. It has four mounting lugs suitable for wall installation and additional knockout for future use. It is suitable for residential (small holding, extensions, garages, outbuildings), Commercial and industrial purposes.



Specification

Items	Parameters
Dimension	L388mm*W259mm*115mm
Power input	AC 230V 50Hz
Socket type	Туре F
Maximum power output	16A
Lamp holder	Screw type E27
RCBO	1pcs 1P+N25A
Minimum Circuit Breaker	1pcs 20A; 1pcs 10A
Material of Ready Board	Injection Molded Plastic
Type of mounting	Wall mounting with four screws
No. of access points for conduit or earth cable	9 at side
Protection class	IP65, IK09
Temperature	-30 to 60℃
Color	Grey
Thickness	Up cover:2.7mm Base:3mm Lamp cover and base:2.8mm


Dimension





PRODUCT INTRODUCTION www.szintersky.com

Components



Lighting chamber cover 0 Chamber Base Lighting chamber base 0 MCB/RCBO Ø € Bulb holder 0 Switch 0 LED bulb Ð Type socket 0 Reflector Transparent turnover Ø Waterproof connector 0 Danger sign B Chamber cover Ø Ø Name plate

Installation Methods

Wall installation

Installation Accessories

Option installation accessories (cost will be different based on the accessories) :



1PCS PG11/M20




4PCS M8*40mm Expand plug 4PCS ST5*35mm Self-tapping screw

Quantity in Different Containers

Quantity
2016
4704

Electrical Diagram



Each Ready Board is packed in a bubble bag, then in a inner box, finally in a carton, the carton is sealed by tape and tie.