

SHENZHEN INTERSKY CO., LTD

Three Phase LV CT Prepayment Metering Unit

ROOM 228A,2ND FLOOR WEST, SCIENCE AND TECHNOLOGY INDUSTRIAL BUILDING, #6 KEYUAN ROAD,HI-TECH PARK, YUEHAI NANSHAN, SHENZHEN, CHINA.

5

 \times

12

SALES@SZINTERSKY.COM

WWW.SZINTERSKY.COM

+86 186 7552 1565

Brief Introduction


TY-MU31 Series metering unit is specially designed for the large power user and can achieve the prepayment function. It is equipped with high precision smart energy meter, which comply with STS standard and have a plug and play communication module for remote reading and controlling; current transformers; MCCB with manual reclose function; Bus bar; Surge arrester equipment and Box for outdoor usage. It is a ideal product for Utilities and Distribution company to reduce energy loss and revenue protection. It is suitable to be used for villa, commercial and industrial projects.



Feature


MCCB with manual reclose Plug and play communication module High accuracy class Maximum demand Split type and recharged through UIU Exchange between postpaid and prepayment mode Outdoor usage

Connection Diagram





OUTLINE DRAWING



SPECIFICATIONS ON METER

DESCRIPTION

Accuracy Rated Voltage Operation voltage range Current Power consumption Protection class

RTC

PARAMETER

Active class 0.5s, reactive class 2.0 3x230/400V.3X240/415V

0.7Un-1.2ur

1(10)A Voltage circuit (Un): 2W/5VA Current circuit (in): 0.5VA

IP54

<is/day (in 23℃)

SPECIFICATIONS ON METER UNIT

200A metering unit

CT ratio	200/5
Box dimension	725mmx252mmx170mm
Weight	Approx. 15kg
Box material	Stainless steel 201
IP protection class	54
300A metering unit	
CT ratio	300/5
Box dimension	700mmx480mmx210mm
Weight	Approx. 23kg
Box material	Stainless steel 201
IP protection class	54

500A metering unit

CT ratio Box dimension Weight Box material IP protection class 500/5 1000mmx800mmx250mm Approx. 54kg Stainless steel 201

54

800A metering unit

CT ratio Box dimension Weight Box material IP protection class 800/5 1000mmx800mmx250mm Approx. 57kg Stainless steel 201

54